

Exam Questions 210-065

CIVND Implementing Cisco Video Network Devices v1.0

<http://www.2passeasy.com/dumps/210-065/>



1.Refer to the exhibit.

Which configuration item shown in the exhibit should be used to assign the internal and external video communication server address for this group of users?

- A. User Settings > Video Address pattern
- B. Administrative Tools > User Settings
- C. Configuration Template > Edit Template
- D. User Import > Configuration

Answer: C

2.Which three features are supported by Cisco TMSPE? (Choose three.)

- A. Simplified provisioning
- B. LDAP user import
- C. Scheduling via Microsoft Outlook
- D. FindMe E. Jabber for Windows
- F. Automatic endpoint upgrades

Answer: A,B,D

3.Management wants to modify Cisco TMS to allow users to configure the call behavior with their associated devices and dial from a single ID. Which feature needs to be enabled and configured?

- A. Smart Scheduler
- B. Low-touch Provisioning
- C. FindMe
- D. CMR Provisioning

Answer: C

4.Which four features are provided by Cisco TelePresence Management Suite? (Choose four.)

- A. Scheduling of video conference calls

- B. Built-in-bridge functionality for multiparty video conferences
- C. SIP-H.323 protocol interworking
- D. Centralized management of conference resources
- E. SMTP email event notification
- F. Endpoint configuration backup and restore
- G. Cisco TelePresence endpoint automated redundancy
- H. Automated resource optimization

Answer: A,D,E,F

5.Which four features are supported by Cisco TelePresence Server for all hardware models in remotely managed mode? (Choose four.)

- A. auto-attendant
- B. ClearPath
- C. Cluster sizes of more than 5 servers
- D. Cascading
- E. Active presence for all devices
- F. Support for Conductor
- G. Native scheduling capabilities

Answer: B,D,E,F

6.A technician is tasked with performing a room readiness assessment in preparation for an immersive video endpoint. What are three Cisco best practices regarding lighting recommendations for the room? (Choose three.)

- A. The bulb temperature should be between 4000 and 4100K.
- B. Key lighting should be between 200 and 400 Lux with the endpoint powered on.
- C. Shoulder lighting should not exceed two times the facial lighting values with the endpoint off.
- D. Use direct lighting fixtures.
- E. Within the camera field of view, the lighting for all parts of the room should not fluctuate more than 100

Lux.

F. Avoid using dimming light control systems.

Answer: A,C,E

7.Which three features does Cisco VCS provide? (Choose three.)

A. native Cisco SCCP telephony integration

B. SIP-H.323 interworking functionality

C. native scheduling

D. SIP trunk integration with Cisco Unified Communications Manager

E. third-party standards-based H.323 and SIP device registration

F. reverse proxy functionality

Answer: B,D,E

8.A network engineer wants to automate the monitoring of Cisco TelePresence TX systems. Which step should the engineer take first?

A. Configure Cisco TMS on the codec.

B. Configure Medianet on the codec.

C. Configure NTP on the codec.

D. Configure Multiway on the codec.

E. Configure SNMP on the codec.

Answer: E

9.Refer to the exhibit.

A network engineer configures a Cisco Unified Communications Manager and VCS integration via a SIP trunk. Endpoint A is able to conduct video calls to Endpoint B. When Endpoint A attempts to share presentation content with Endpoint B, Endpoint B sees the presentation video on the main screen rather than on the presentation display. What is the cause?

A. The default MTP telephony payload is incorrect.

- B. The SIP trunk is not running on all active Cisco Unified Communications Manager nodes.
- C. MTP is not forced to be required.
- D. BFCP is not enabled.
- E. The MTP preferred codec is incorrect for content presentation.

Answer: D

10. A Unified Communications engineer wants to configure a Cisco TelePresence SX endpoint using static IP addressing to use a different TFTP server. Which path will allow the engineer to complete this configuration?

- A. Network Services > Network 1 > DHCP RequestTFTPServerAddress > Off
- B. Network > TFTP > DHCP RequestTFTPServerAddress > Off
- C. Network Services > TFTP > DHCP RequestTFTPServerAddress > Off
- D. Configuration > System Configuration > Provisioning > Set the External Manager Address

Answer: D

11. Which two protocols can be used with the Cisco TelePresence Content Server to allow users to share content from their laptops? (Choose two.)

- A. BFCP
- B. H.239
- C. PCoIP
- D. Switched Presentation
- E. SCCP
- F. RDP

Answer: A,B

12. A technician has installed and powered on a Cisco TelePresence MCU 5320 and is connected via the console port. The technician needs to determine the IP settings that were automatically assigned via DHCP. Which command should be entered?

- A. xstatus
- B. show network eth0
- C. status
- D. help static

Answer: C

13. An engineer is creating a system backup on a Cisco VCS. Which two options describe characteristics of Cisco VCS backups? (Choose two.)

- A. The backup can be sent to the remote SFTP server.
- B. The backup can be encrypted with a password.
- C. The backup can be sent to additional servers in the cluster.
- D. The backup is valid for 30 days.
- E. The backup is stored in Cisco TMS.
- F. The backup is only downloadable locally.

Answer: B,F

14. Cisco TMS is unable to manage endpoints and an engineer is required to capture logs to determine the cause. What is the menu path that the engineer should follow to capture and download logs from Cisco TMS?

- A. Administrative Tools > Diagnostics > TMS Tickets
- B. Administrative Tools > TMS Server Maintenance > Download Diagnostic Files
- C. Systems > Navigator > Diagnostics > Download Diagnostic Files
- D. Systems > Navigator > TMS Logs

Answer: B

15. A Cisco TelePresence VCS displays this alarm: "Root password is set to default." How can this security warning be addressed?

- A. Use the Cisco TelePresence VCS web user interface, choose Administration > User Settings, and change the root password.

B. Use SSH to log in to the Cisco TelePresence VCS as Administrator and issue the command `xconfig root set passwd`.

C. Use SSH to log in to the Cisco TelePresence VCS as Root, issue the command `set password`, and enter the new password when prompted.

D. Use SSH to log in to the Cisco TelePresence VCS as Root, issue the command `passwd`, and enter the new password when prompted.

E. Use the Cisco TelePresence VCS web user interface, choose Administration > System Settings, and change the root password.

Answer: D

THANKS FOR TRYING THE DEMO OF OUR PRODUCT

Visit Our Site to Purchase the Full Set of Actual 210-065 Exam Questions With Answers.

We Also Provide Practice Exam Software That Simulates Real Exam Environment And Has Many Self-Assessment Features. Order the 210-065 Product From:

<http://www.2passeasy.com/dumps/210-065/>

Money Back Guarantee

210-065 Practice Exam Features:

- * 210-065 Questions and Answers Updated Frequently
- * 210-065 Practice Questions Verified by Expert Senior Certified Staff
- * 210-065 Most Realistic Questions that Guarantee you a Pass on Your FirstTry
- * 210-065 Practice Test Questions in Multiple Choice Formats and Updatesfor 1 Year