

Exam Questions 300-101

ROUTE Implementing Cisco IP Routing

<http://www.2passeasy.com/dumps/300-101/>



1. When using SNMPv3 with NoAuthNoPriv, which string is matched for authentication?

- A. username
- B. password
- C. community-string
- D. encryption-key

Answer: A

2. A network engineer is configuring a solution to allow failover of HSRP nodes during maintenance windows, as an alternative to powering down the active router and letting the network respond accordingly. Which action will allow for manual switching of HSRP nodes?

- A. Track the up/down state of a loopback interface and shut down this interface during maintenance.
- B. Adjust the HSRP priority without the use of preemption.
- C. Disable and enable all active interfaces on the active HSRP node.
- D. Enable HSRPv2 under global configuration, which allows for maintenance mode.

Answer: A

3. A company's corporate policy has been updated to require that stateless, 1-to-1, and IPv6 to IPv6 translations at the Internet edge are performed. What is the best solution to ensure compliance with this new policy?

- A. NAT64
- B. NAT44
- C. NATv6
- D. NPTv4
- E. NPTv6

Answer: E

4. What is a function of NPTv6?

- A. It interferes with encryption of the full IP payload.
- B. It maintains a per-node state.
- C. It is checksum-neutral.

D. It rewrites transport layer headers.

Answer: C

5. An organization decides to implement NetFlow on its network to monitor the fluctuation of traffic that is disrupting core services. After reviewing the output of NetFlow, the network engineer is unable to see OUT traffic on the interfaces. What can you determine based on this information?

A. Cisco Express Forwarding has not been configured globally.

B. NetFlow output has been filtered by default.

C. Flow Export version 9 is in use.

D. The command `ip flow-capture fragment-offset` has been enabled.

Answer: A

6. A network engineer initiates the `ip sla responder tcp-connect` command in order to gather statistics for performance gauging. Which type of statistics does the engineer see?

A. connectionless-oriented

B. service-oriented

C. connection-oriented

D. application-oriented

Answer: C

7. A network engineer is trying to implement broadcast-based NTP in a network and executes the `ntp broadcast client` command. Assuming that an NTP server is already set up, what is the result of the command?

A. It enables receiving NTP broadcasts on the interface where the command was executed.

B. It enables receiving NTP broadcasts on all interfaces globally.

C. It enables a device to be an NTP peer to another device.

D. It enables a device to receive NTP broadcast and unicast packets.

Answer: A

8. Refer to the exhibit.

```
Sampler : mysampler, id : 1, packets matched : 10, mode :  
random sampling mode
```

Which statement about the output of the show flow-sampler command is true?

- A. The sampler matched 10 packets, each packet randomly chosen from every group of 100 packets.
- B. The sampler matched 10 packets, one packet every 100 packets.
- C. The sampler matched 10 packets, each one randomly chosen from every 100-second interval.
- D. The sampler matched 10 packets, one packet every 100 seconds.

Answer: A

9. A network engineer is asked to configure a "site-to-site" IPsec VPN tunnel. One of the last things that the engineer does is to configure an access list (access-list 1 permit any) along with the command ip nat inside source list 1 int s0/0 overload. Which functions do the two commands serve in this scenario?

- A. The command access-list 1 defines interesting traffic that is allowed through the tunnel.
- B. The command ip nat inside source list 1 int s0/0 overload disables "many-to-one" access for all devices on a defined segment to share a single IP address upon exiting the external interface.
- C. The command access-list 1 permit any defines only one machine that is allowed through the tunnel.
- D. The command ip nat inside source list 1 int s0/0 overload provides "many-to-one" access for all devices on a defined segment to share a single IP address upon exiting the external interface.

Answer: D

10. IPv6 has just been deployed to all of the hosts within a network, but not to the servers. Which feature allows IPv6 devices to communicate with IPv4 servers?

- A. NAT
- B. NATng
- C. NAT64
- D. dual-stack NAT
- E. DNS64

Answer: C

11. Which type of traffic does DHCP snooping drop?

- A. discover messages
- B. DHCP messages where the source MAC and client MAC do not match
- C. traffic from a trusted DHCP server to client
- D. DHCP messages where the destination MAC and client MAC do not match

Answer: B

12. Which two methods of deployment can you use when implementing NAT64? (Choose two.)

- A. stateless
- B. stateful
- C. manual
- D. automatic
- E. static
- F. functional
- G. dynamic

Answer: A,B

13. A network engineer is configuring SNMP on network devices to utilize one-way SNMP notifications. However, the engineer is not concerned with authentication or encryption. Which command satisfies the requirements of this scenario?

- A. `router(config)#snmp-server host 172.16.201.28 traps version 2c CISCORO`
- B. `router(config)#snmp-server host 172.16.201.28 informs version 2c CISCORO`
- C. `router(config)#snmp-server host 172.16.201.28 traps version 3 auth CISCORO`
- D. `router(config)#snmp-server host 172.16.201.28 informs version 3 auth CISCORO`

Answer: A

14. A network engineer is notified that several employees are experiencing network performance related issues, and bandwidth-intensive applications are identified as the root cause. In order to identify which specific type of traffic is causing this slowness, information such as the source/destination IP and Layer 4 port numbers is required. Which feature should the engineer use to gather the required information?

- A. SNMP
- B. Cisco IOS EEM
- C. NetFlow
- D. Syslog
- E. WCCP

Answer: C

15. After a recent DoS attack on a network, senior management asks you to implement better logging functionality on all IOS-based devices. Which two actions can you take to provide enhanced logging results? (Choose two.)

- A. Use the msec option to enable service time stamps.
- B. Increase the logging history .
- C. Set the logging severity level to 1.
- D. Specify a logging rate limit.
- E. Disable event logging on all noncritical items.

Answer: A,B

THANKS FOR TRYING THE DEMO OF OUR PRODUCT

Visit Our Site to Purchase the Full Set of Actual 300-101 Exam Questions With Answers.

We Also Provide Practice Exam Software That Simulates Real Exam Environment And Has Many Self-Assessment Features. Order the 300-101 Product From:

<http://www.2passeasy.com/dumps/300-101/>

Money Back Guarantee

300-101 Practice Exam Features:

- * 300-101 Questions and Answers Updated Frequently
- * 300-101 Practice Questions Verified by Expert Senior Certified Staff
- * 300-101 Most Realistic Questions that Guarantee you a Pass on Your FirstTry
- * 300-101 Practice Test Questions in Multiple Choice Formats and Updatesfor 1 Year